



# PRODUCT INFORMATION

**PART #**

**BS-TRA**

**Revision: 0-2012**

## 9 V Cell Connector, Safety, "T" Style



**ISO 9001**

### SPECIFICATIONS



<b>Battery (Cell) Type</b>	<b>9V</b>		<b>Number of Cells</b>	<b>1</b>	
<b>Cell Configuration</b>	<b>Series Connection</b>		<b>Output Voltage</b>	<b>9 Vdc</b>	
<b>Operating Temperature</b>	<b>-20°C to + 65°C</b>		<b>Storage Temperature</b>	<b>-30°C to +85°C</b>	
<b>Material</b>	<b>Case</b>	<b>Plastic, ABS Resin, Black</b>		<b>Washer</b>	
	<b>Contact</b>	<b>6 Prongs Snap Terminal</b>			
	<b>Termination</b>	<b>Wire Leads, 26 AWG, UL 1007, Stranded, 150 ± 5 mm, Stripped and Tinned 5 ± 1 mm</b>			
<b>Physical Dimensions</b>	<b>Length (L)</b>	<b>24.5 mm</b>	<b>Width (W)</b>	<b>13.5 mm</b>	<b>Height (H)</b> <b>7.6 mm</b>
<b>Approximate Weight</b>	<b>grams</b>		<b>Compliance</b>	<b>RoHS</b>	
<b>Options</b>					

### RELIABILITY

<b>Insulation Test</b>	A minimum of 10 MΩ, measured with 100 Vdc Insulation Resistance Meter, between the Electrical Terminals and the Case
<b>Vibration Test</b>	2 Hours of at 1.5 mm with 10 to 55 Hz. vibration frequency to each of 3 perpendicular directions
<b>Termination Strength</b>	Maximum of 9.8 N (1.0 Kg) load pull test, applied to each terminal in axial direction for 10 seconds
<b>Drop Test</b>	Dropped naturally from 750 mm height onto the surface of 40 mm wooden board, 3 axes (X,Y,Z) directions, 3 times (6 times total)
<b>Warranty</b>	For a period of one (1) year from date of shipping under normal operations conditions

### DIMENSIONS

**Dimensions in mm; Tolerance ±0.5 mm**

