



PRODUCT INFORMATION

PART #	BH-333P	Revision: 0-2012
	3 AA Batteries Holder	image not available
ISO 9001		

SPECIFICATIONS


Battery (Cell) Type	AA	Number of Cells	3			
Cell Configuration	Series Connection	Output Power	4.5 Vdc			
Operating Temperature	-20°C to + 65°C	Storage Temperature	-30°C to +85°C			
Material	Case	Plastic, PP Resin, Black	Washer			
	Contact	SPRING: 0.7MM 65C Spring wire, nickel-plated				
	Termination	PC PIN				
Physical Dimensions	Length (L)	158 mm	Width (W)	17 mm	Height (H)	14 mm
Approximate Weight	grams		Compliance	RoHS		
Options						

RELIABILITY

Insulation Test	A minimum of 10 MΩ, measured with 100 Vdc Insulation Resistance Meter, between the Electrical Terminals and the Case
Vibration Test	2 Hours of at 1.5 mm with 10 to 55 Hz. vibration frequency to each of 3 perpendicular directions
Termination Strength	Maximum of 9.8 N (1.0 Kg) load pull test, applied to each terminal in axial direction for 10 seconds
Drop Test	Dropped naturally from 750 mm height onto the surface of 40 mm wooden board, 3 axes (X,Y,Z) directions, 3 times (6 times total)
Warranty	For a period of one (1) year from date of shipping under normal operations conditions

DIMENSIONS

Dimensions in mm; Tolerance ±0.5 mm



SPECIFICATION

- (1) ITEM NO: BH-333P
- (2) HOLDER MATERIAL: P. P. RESIN, BLACK COLOR
- (3) WITH PIN: 0. 8X24MM, BRASS NICKEL PLATED
- (4) SPRING: 0. 7MM 65C SPRING WIRE NICKEL PLATED
- (5) RIVET: BRASS NICKEL PLATED
- (6) RoHS COMPLIANT