



# PRODUCT INFORMATION

<b>PART #</b>	<b>BH-341-1B6</b>	<b>Revision: 0-2014</b>
---------------	-------------------	-------------------------

 <b>ISO 9001</b>	<b>4 AA Batteries Holder</b>
---------------------	------------------------------


## SPECIFICATIONS

Battery (Cell) Type	AA	Number of Cells	4			
Cell Configuration	Series Connection	Output Voltage	6 Vdc			
Operating Temperature	-20°C to + 65°C	Storage Temperature	-30°C to +85°C			
Material	Case	Plastic, PP Resin, Black	Washer			
	Contact	Springs 0.6 mm, 65C spring wire				
	Termination	6 Prong SNAP				
Physical Dimensions	Length (L)	63.1 mm	Width (W)	58.0 mm	Height (H)	16.0 mm
Approximate Weight	grams			Compliance	RoHS	
Options						

## RELIABILITY

Insulation Test	A minimum of 10 MΩ, measured with 100 Vdc Insulation Resistance Meter, between the Electrical Terminals and the Case
Vibration Test	2 Hours of at 1.5 mm with 10 to 55 Hz. vibration frequency to each of 3 perpendicular directions
Termination Strength	Maximum of 9.8 N (1.0 Kg) load pull test, applied to each terminal in axial direction for 10 seconds
Drop Test	Dropped naturally from 750 mm height onto the surface of 40 mm wooden board, 3 axes (X,Y,Z) directions, 3 times (6 times total)
Warranty	For a period of one (1) year from date of shipping under normal operations conditions

## DIMENSIONS



Revision	Description	By	Date

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.

Copyright © 2014 Challenge Electronics