





# PRODUCT INFORMATION

<b>PART #</b>	<b>BH-411A</b>	<b>Revision: 1-2011</b>
	<b>1 AAA Battery Holder</b>	
<b>ISO 9001</b>		

## SPECIFICATIONS

<b>Battery (Cell) Type</b>	AAA		<b>Number of Cells</b>	1		
<b>Cell Configuration</b>	Series Connection		<b>Output Voltage</b>	1.5 Vdc		
<b>Operating Temperature</b>	-20°C to + 65°C		<b>Storage Temperature</b>	-30°C to +85°C		
<b>Material</b>	<b>Case</b>	Plastic, PP Resin, Black				
	<b>Contact</b>	Springs — 0.8 mm, 65 C Spring Wire				
	<b>Termination</b>	Wire Leads, 26 AWG, UL 1007, Stranded, 150 ± 5 mm, Stripped and Tinned 5 ± 1 mm				
<b>Physical Dimensions</b>	<b>Length (L)</b>	50.0 mm	<b>Width (W)</b>	13.0 mm	<b>Height (H)</b>	12.0 mm
<b>Approximate Weight</b>	grams		<b>Compliance</b>	RoHS		
<b>Options</b>						

## RELIABILITY

<b>Insulation Test</b>	A minimum of 10 MΩ, measured with 100 Vdc Insulation Resistance Meter, between the Electrical Terminals and the Case
<b>Vibration Test</b>	2 Hours of at 1.5 mm with 10 to 55 Hz. vibration frequency to each of 3 perpendicular directions
<b>Termination Strength</b>	Maximum of 9.8 N (1.0 Kg) load pull test, applied to each terminal in axial direction for 10 seconds
<b>Drop Test</b>	Dropped naturally from 750 mm height onto the surface of 40 mm wooden board, 3 axes (X,Y,Z) directions, 3 times (6 times total)
<b>Warranty</b>	For a period of one (1) year from date of shipping under normal operations conditions

## DIMENSIONS

