



PRODUCT INFORMATION

PART #	BH-432	Revision: 0-2012
---------------	---------------	-------------------------



3 AAA Batteries Holder



SPECIFICATIONS

Battery (Cell) Type	AAA		Number of Cells	3	
Cell Configuration	Series Connection		Output Power	4.5 Vdc	
Operating Temperature	-20°C to + 65°C		Storage Temperature	-30°C to +85°C	
Material	Case	Plastic, ABS Resin, Black			
	Contact	Springs, 0.5 mm, 65C			
	Termination	Contact # 407, Brass Nickel Plated			
Physical Dimensions	Length (L)	56.6 mm	Width (W)	Height (H)	22.3 mm ϕ
Approximate Weight	grams		Compliance	RoHS	
Options					

RELIABILITY

Insulation Test	A minimum of 10 M Ω , measured with 100 Vdc Insulation Resistance Meter, between the Electrical Terminals and the Case
Vibration Test	2 Hours of at 1.5 mm with 10 to 55 Hz. vibration frequency to each of 3 perpendicular directions
Termination Strength	Maximum of 9.8 N (1.0 Kg) load pull test, applied to each terminal in axial direction for 10 seconds
Drop Test	Dropped naturally from 750 mm height onto the surface of 40 mm wooden board, 3 axes (X,Y,Z) directions, 3 times (6 times total)
Warranty	For a period of one (1) year from date of shipping under normal operations conditions

DIMENSIONS

Dimensions in mm; Tolerance ± 0.5 mm

