



PRODUCT INFORMATION

PART #	BH-221D	Revision: 0-2012
---------------	----------------	-------------------------

 ISO 9001	<h2 style="margin: 0;">2 C Batteries Holder</h2>	Image not available
---------------------	--	---------------------

SPECIFICATIONS			
Battery (Cell) Type	C	Number of Cells	2
Cell Configuration	Series Connection	Output Voltage	3 Vdc
Operating Temperature	-20°C to + 65°C	Storage Temperature	-30°C to +85°C
Material	Case Plastic, PP Resin, Black		
	Contact Two (2) Springs, 0.8 mm, 65C Spring Wire		
	Termination Solder Tab/Lug		
Physical Dimensions	Length (L) 62.5 mm	Width (W) 55.8 mm	Height (H) 23.5 mm
Approximate Weight	grams	Compliance	RoHS
Options			

RELIABILITY	
Insulation Test	A minimum of 10 MΩ, measured with 100 Vdc Insulation Resistance Meter, between the Electrical Terminals and the Case
Vibration Test	2 Hours of at 1.5 mm with 10 to 55 Hz. vibration frequency to each of 3 perpendicular directions
Termination Strength	Maximum of 9.8 N (1.0 Kg) load pull test, applied to each terminal in axial direction for 10 seconds
Drop Test	Dropped naturally from 750 mm height onto the surface of 40 mm wooden board, 3 axes (X,Y,Z) directions, 3 times (6 times total)
Warranty	For a period of one (1) year from date of shipping under normal operations conditions

DIMENSIONS	Dimensions in mm; Tolerance ±0.5 mm
------------	-------------------------------------

SPECIFICATION

- (1) ITEM NO.: BH-221D
- (2) WITH SOLDER TERMINAL
- (3) MATERIAL: P.P. RESIN ,BLACK COLOR
- (4) SPRING: 0.8 MM 65C SPRING WIRE