



PRODUCT INFORMATION

PART #	BH-181-2D	Revision: 1-2013
	8 "D" Batteries Holder	
ISO 9001		

SPECIFICATIONS


Battery (Cell) Type	D		Number of Cells	8		
Cell Configuration	Series Connection		Output Power	12.0 Vdc		
Operating Temperature	-20°C to + 65°C		Storage Temperature	-30°C to +85°C		
Material	Case	P.P. Resin (black)		Washer		
	Contact	0.9 mm 65C Spring Wire				
	Termination	Solder Tabs				
Physical Dimensions	Length (L)	142	Width (W)	73	Height (H)	62
Approximate Weight			Compliance	RoHS		
Options						

RELIABILITY

Insulation Test	A minimum of 10 MΩ, measured with 100 Vdc Insulation Resistance Meter, between the Electrical Terminals and the Case
Vibration Test	2 Hours of at 1.5 mm with 10 to 55 Hz. vibration frequency to each of 3 perpendicular directions
Termination Strength	Maximum of 9.8 N (1.0 Kg) load pull test, applied to each terminal in axial direction for 10 seconds
Drop Test	Dropped naturally from 750 mm height onto the surface of 40 mm wooden board, 3 axes (X,Y,Z) directions, 3 times (6 times total)
Warranty	For a period of one (1) year from date of shipping under normal operations conditions

DIMENSIONS

Dimensions in mm; Tolerance ±0.5 mm



The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.

Copyright © 2012 Challenge Electronics