



PRODUCT INFORMATION

PART #	BC-0301	Revision: 0-2013
---------------	----------------	-------------------------

 ISO 9001	“AA” PCB Snap-In Battery Clip # 0301
---------------------	---


SPECIFICATIONS

Battery (Cell) Type	“AA”	Number of Contacts	1
Operating Temperature	-30°C to + 85°C	Storage Temperature	-40°C to +95°C
Contact Material	Steel with Nickel Plating, 0.3 mm thickness		
Approximate Weight	grams	Compliance	RoHS
Options			

RELIABILITY

Insulation Test	A minimum of 10 MΩ, measured with 100 Vdc Insulation Resistance Meter, between the Electrical Terminals and the Case
Vibration Test	2 Hours of at 1.5 mm with 10 to 55 Hz. vibration frequency to each of 3 perpendicular directions
Termination Strength	Maximum of 9.8 N (1.0 Kg) load pull test, applied to each terminal in axial direction for 10 seconds
Drop Test	Dropped naturally from 750 mm height onto the surface of 40 mm wooden board, 3 axes (X,Y,Z) directions, 3 times (6 times total)
Warranty	For a period of one (1) year from date of shipping under normal operations conditions

DIMENSIONS



Revision	Description	By	Date
1-2013	Original Specification	Walter Sargent	9/30/2013