



## PRODUCT INFORMATION

<b>PART #</b>	<b>CONTACT-202A</b>	<b>Revision: 0-2012</b>
 <b>ISO 9001</b>	<h1># 202 Anode Battery Contact</h1>	

### SPECIFICATIONS

Battery (Cell) Type	202	Number of Contacts	1 Anode
Operating Temperature	-30°C to + 85°C	Storage Temperature	-40°C to +95°C
Contact Material	0.5 mm Thick, Steel with Nickel Plating		
Approximate Weight	grams	Compliance	RoHS
Options			

### RELIABILITY

Insulation Test	A minimum of 10 MΩ, measured with 100 Vdc Insulation Resistance Meter, between the Electrical Terminals and the Case
Vibration Test	2 Hours of at 1.5 mm with 10 to 55 Hz. vibration frequency to each of 3 perpendicular directions
Termination Strength	Maximum of 9.8 N (1.0 Kg) load pull test, applied to each terminal in axial direction for 10 seconds
Drop Test	Dropped naturally from 750 mm height onto the surface of 40 mm wooden board, 3 axes (X,Y,Z) directions, 3 times (6 times total)
Warranty	For a period of one (1) year from date of shipping under normal operations conditions

### DIMENSIONS

Dimensions in mm; Tolerance ±0.5 mm

