



PRODUCT INFORMATION

PART # **CE-G1.1**

Revision: **0-2010**

DESCRIPTION:

RUBBER GASKET, hermetically seals the panel with the **CE SERIES** of **PIEZELECTRIC ALARMS** of A or B case. With the Rubber Gasket, the assembly will meet **ASTM B117, IP 68, NEMA 3R, 4X, and 12** for Water Proof and Dust Exposure.

FEATURES:

- ◆ **Extended storage temperature.**
- ◆ **Hermetically Seals the Alarm.**
- ◆ **Withstands exposure to salt spray Per ASTM B117.**
- ◆ **Water Proof and Dust Exposure, per IP-68 & NEMA 3R, 4X, and 12, with Gasket (not supplied) any case A, B, or K.**
- ◆ **RoHS Compliance.**
- ◆ **ISO 9001 Certified.**

SPECIFICATIONS:

Material:	Neoprene		Color:	Black		
Dimensions:	Outside Diameter:	34.3 mm	Inside Diameter:	28.6 mm	Thickness:	3.2 mm
Tensile:	1,300 PSI Minimum		Elongation:	300% Minimum		
Flammability:	UL-94-HBF		Temperature Range:	-40°C to +105°C		
Approximate Weight:	0.5 grams		Compliance:	RoHS		
Packaging:						
Warranty:	For a period of one (1) year from date of manufacture under normal operating conditions.					
Assembly Instruction:	<ol style="list-style-type: none"> 1. Remove the Ring Nut from the alarm. 2. Place the Rubber Gasket in the front of the alarm. . 3. Push the gasket all the way on top of the threads. 4. Push the alarm with the Gasket into the Mounting Hole in your Panel. 5. Install the Ring Nut into the alarm threads and tighten the Ring Nut as much as possible. 6. The Gasket is compressed and seals the interior of the panel from outside environment. 					
Note:	It is recommended that one of the alarm Sound Port opening should be Mounted at the lowest point of the Panel to help with water drainage.					

