



PRODUCT INFORMATION

Part #: **CE-BCM530AWS**

Revision: 5-2014



DESCRIPTION		FEATURES				
Challenge Electronics Dual Function BEEP or CONTINUOUS Tone; MEDIUM Loud Piezoelectric Alarm; 5 to 30 Vdc; A style Rear Panel Mount case; Sound Pressure Level of 97 dB(A) at 30 Vdc at 61 cm; 2,900 Hz. Output Frequency; Wire Leads 5" Long termination; Slow Beep, 1 pulse per second Rate; RoHS Compliant		<ul style="list-style-type: none"> ◆ Reliable Solid State Piezoelectric Technology ◆ Corrosion resistant Stainless Steel Diaphragm ◆ Flame Retardant Plastic ◆ Extended storage temperature ◆ Hermetically Sealed Alarm ◆ Water Proof, NEMA 3R, 4X, or 12 with Gasket (not supplied) ◆ RoHS, Lead Free Compliance ◆ ISO 9001:2008 & ISO-TS 16949:2009 Certified 				
SPECIFICATIONS						
Operating Mode	Medium Loud, Slow Intermittent or Continuous Tones		Pulse Rate	1 ± 10% Pulse per Second		
Operating Voltage	5 to 30 Vdc	Nominal Operating Voltage	24 Vdc	Operating Frequency	2,900 ± 250 Hz.	
Typical Loudness	At 5 Vdc	84±5 dB(A)	At 24 Vdc	97±3 dB(A)	At 30 Vdc	97±3 dB(A)
	SPL is measured at 24" (61 cm), 25°C, Sound Level meter # 2240, Type 2, Fast Response, A-Weighted					
Typical Operating Current	5 mA at 5 Vdc		25 mA at 24 Vdc		30 mA at 30 Vdc	
Operating Temperature	-30°C to +65°C		Storage Temperature	-40°C to +100°C		
Surge Voltage	20% over maximum Operating Voltage for less than 5 minutes					
Polarity Protection	Protected against Reversed Voltage to the Maximum Operating Voltage					
Materials	Alarm Case	Plastic, "A" Case, NORYL™, PX9406 or equal, flame retardant UL 94-V0, Black				
	Diaphragm	Stainless Steel 304				
	Encapsulation	Silicon Potting covering SMD components topped with 2 parts epoxy potting, Black				
	Termination	Three (3) Wires Leads, 18 AWG (7X32), GXL Automotive, Copper, XPLE insulated, 5.0" (127) Long. Struck 0.235 (6.0mm), Red = Common Positive Black = Intermittent Negative, and Blue = Continuous Negative				
Physical Dimensions	Diameter	1.4" (35.6 mm) Ø		Width	Height	1.4" (35.7 mm)
Panel Mounting	From the Rear with Plastic Ring Nut		Mounting Hole	1.125" (28.6mm) Ø	Max. Panel Thickness	0.25" (6.3 mm)
Approximate Weight	37 grams	Rotor Volume Control	No	Compliance	RoHS	
Available Options	Rotor Volume Control, Water Proof Gasket, Mounting Bracket, and variety of connectors terminated on the Wire Lead ends					
RELIABILITY						
Thermal Operating Temperature Test	96 hours continuous operation at Rated Voltage, at Maximum Rated Operating Temperature *					
	96 hours continuous operation at Rated Voltage, at Minimum Rated Operating Temperature *					
Thermal Storage Temperature Test	96 hours storage at Maximum Rated Storage Temperatures *					
	96 hours storage at Minimum Rated Storage Temperatures *					
Thermal Shock Test	5 cycles of Minimum and Maximum Operating Temperature Each cycle shall be set per diagram below and is 3 hours long *					
Humidity Test	120 Hours at +60°C±2°C. 90-95% RH *					
Salt Spray	Withstand exposure to salt spray per ASTM B117 for a period of 300 hours *					
Water & Dust Exposure	Withstands water submergence and dust exposure per IP-68 *					
Vibration Test	2 Hours at 1.5 mm with 10 to 55 Hz. of vibration frequency to each of 3 perpendicular direction *					
Drop Test	Dropped naturally from 1 meter height onto the surface of 10mm wooden board, 2 directions upper and side of the part are applied *					
Termination Strength	Maximum of 15 pounds (6.8 Kg) load pull test					
* Reliability Test Performance	Parts should conform to original performance within ±3 dB, after 3 hours of recovery and dry period					
Life Test	Intermittent	1,000 hours of a 1 minute on 4 minutes off cycle at room temperature and maximum rated Voltage				
	Continuous	250 hours continuous operation at room temperature and maximum rated Voltage				
Warranty	For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair					



Current Draw and Loudness Vs. Input Voltage		DIMENSIONS		Units	Inches (mm)	Tolerance	0.030 (0.7)																																
ALARM MAKING				TYPICAL MOUNTING																																			
<p>On side Case:</p> <p>Part Number Sound Type Operating Voltage Range / Date Code Challenge Electronics Made in China</p> <p>On Back:</p> <p>Polarity</p>				<table border="1"> <tr> <td>Alarm Threads:</td> <td>1.125-24 UNF Threads, 2A Class, Major 1.118" Ø, Minor 1.063" Ø, Pitch 1.094" Ø</td> </tr> <tr> <td>Ring Nut Threads:</td> <td>1.125-24 UNF Threads, 2B Class, Major 1.120" Ø, Minor 1.073" Ø, Pitch 1.094" Ø</td> </tr> <tr> <td>Mounting Hole:</td> <td>1.25" (31.75 mm) Ø</td> </tr> <tr> <td>Panel Thickness:</td> <td>0.03 (0.75 mm) to 0.25" (6.4 mm)</td> </tr> <tr> <td>Gasket (Optional):</td> <td>1.25" (31.75 mm) ID, 1.40" (35.6 mm) OD, 0.10" (2.54 mm) Thick Rubber,</td> </tr> </table>				Alarm Threads:	1.125-24 UNF Threads, 2A Class, Major 1.118" Ø, Minor 1.063" Ø, Pitch 1.094" Ø	Ring Nut Threads:	1.125-24 UNF Threads, 2B Class, Major 1.120" Ø, Minor 1.073" Ø, Pitch 1.094" Ø	Mounting Hole:	1.25" (31.75 mm) Ø	Panel Thickness:	0.03 (0.75 mm) to 0.25" (6.4 mm)	Gasket (Optional):	1.25" (31.75 mm) ID, 1.40" (35.6 mm) OD, 0.10" (2.54 mm) Thick Rubber,																						
Alarm Threads:	1.125-24 UNF Threads, 2A Class, Major 1.118" Ø, Minor 1.063" Ø, Pitch 1.094" Ø																																						
Ring Nut Threads:	1.125-24 UNF Threads, 2B Class, Major 1.120" Ø, Minor 1.073" Ø, Pitch 1.094" Ø																																						
Mounting Hole:	1.25" (31.75 mm) Ø																																						
Panel Thickness:	0.03 (0.75 mm) to 0.25" (6.4 mm)																																						
Gasket (Optional):	1.25" (31.75 mm) ID, 1.40" (35.6 mm) OD, 0.10" (2.54 mm) Thick Rubber,																																						
PACKAGING				MARKING																																			
<p>ONE TRAY:</p>		<p>TWO BUNDLE</p>		<p>TRAY</p> <table border="1"> <tr> <td>X1</td> <td>34.7 cm</td> </tr> <tr> <td>Y1</td> <td>34.7 cm</td> </tr> <tr> <td>Z1</td> <td>21.2 cm</td> </tr> </table>		X1	34.7 cm	Y1	34.7 cm	Z1	21.2 cm	<p>BUNDLE</p> <table border="1"> <tr> <td>X2</td> <td>cm</td> </tr> <tr> <td>Y2</td> <td>cm</td> </tr> <tr> <td>Z2</td> <td>cm</td> </tr> </table>		X2	cm	Y2	cm	Z2	cm																				
X1	34.7 cm																																						
Y1	34.7 cm																																						
Z1	21.2 cm																																						
X2	cm																																						
Y2	cm																																						
Z2	cm																																						
<p>ONE BUNDLE:</p>		<p>SHIPPING BOX</p>		<p>SHIPPING BOX</p> <table border="1"> <tr> <td>X3</td> <td>35 cm</td> </tr> <tr> <td>Y3</td> <td>35 cm</td> </tr> <tr> <td>Z3</td> <td>22.5 cm</td> </tr> </table>		X3	35 cm	Y3	35 cm	Z3	22.5 cm	<p>SHIPPING BOX</p> <table border="1"> <tr> <td>Quantity</td> <td>42</td> </tr> <tr> <td>Lot and/or Date Code</td> <td></td> </tr> <tr> <td>Bundle Number</td> <td></td> </tr> <tr> <td>Shipping Box</td> <td></td> </tr> <tr> <td>Part Number</td> <td></td> </tr> <tr> <td>Other PN (if required)</td> <td></td> </tr> <tr> <td>Quantity</td> <td></td> </tr> <tr> <td>Lot and/or Date Code</td> <td></td> </tr> <tr> <td>PO Number</td> <td></td> </tr> <tr> <td>Net Weight</td> <td></td> </tr> <tr> <td>Gross Weight</td> <td>1</td> </tr> <tr> <td>Box Number of Boxes</td> <td>250</td> </tr> <tr> <td>Made in China</td> <td>9 Kg.</td> </tr> </table>		Quantity	42	Lot and/or Date Code		Bundle Number		Shipping Box		Part Number		Other PN (if required)		Quantity		Lot and/or Date Code		PO Number		Net Weight		Gross Weight	1	Box Number of Boxes	250	Made in China	9 Kg.
X3	35 cm																																						
Y3	35 cm																																						
Z3	22.5 cm																																						
Quantity	42																																						
Lot and/or Date Code																																							
Bundle Number																																							
Shipping Box																																							
Part Number																																							
Other PN (if required)																																							
Quantity																																							
Lot and/or Date Code																																							
PO Number																																							
Net Weight																																							
Gross Weight	1																																						
Box Number of Boxes	250																																						
Made in China	9 Kg.																																						
<p>TOP COVER</p>		<p>ITEM: C/Nº: MADE IN CHINA</p> <table border="1"> <tr> <td>MODEL</td> <td>PCS</td> </tr> <tr> <td>QTY</td> <td>KG</td> </tr> <tr> <td>N.W</td> <td>KG</td> </tr> <tr> <td>G.W</td> <td>KG</td> </tr> <tr> <td>SIZE</td> <td></td> </tr> <tr> <td>LOT NO</td> <td></td> </tr> </table>		MODEL	PCS	QTY	KG	N.W	KG	G.W	KG	SIZE		LOT NO		<p>Quantity</p>		42																					
MODEL	PCS																																						
QTY	KG																																						
N.W	KG																																						
G.W	KG																																						
SIZE																																							
LOT NO																																							
Lot and/or Date Code																																							
Bundle Number																																							
Shipping Box																																							
Part Number																																							
Other PN (if required)																																							
Quantity																																							
Lot and/or Date Code																																							
PO Number																																							
Net Weight																																							
Gross Weight	1																																						
Box Number of Boxes	250																																						
Made in China	9 Kg.																																						

Revision	**Description**	**By**	**Date**
3-2011	Modified Dimensions Drawing	Ely Zofan	5/10/2011
4-2012	Updated Specifications	Ely Zofan	12/17/2012
5-2014	Updated Specifications	Ely Zofan	6/18/2014