



PRODUCT INFORMATION

Part #: **CE-WM530ASF**

Revision: 3-2012



DESCRIPTION		FEATURES			
Challenge Electronics WARBLE Tone, MEDIUM Loud, 5 to 30 Vdc, A style case Rear Panel Mounting in 1.125" (28.6 mm) Hole, Sound Pressure Level of 98 dB(A) at 30 Vdc at 61 cm, 2,900 Hz. Output Frequency, S two 0.25" (6.4 mm) Blades with M3 0.25" (6.4 mm) long Stainless Steel Screws termination, Fast Rate 3 cycles per second, Piezoelectric Alarm, RoHS Compliant		<ul style="list-style-type: none"> ◆ Reliable Solid State Piezoelectric Technology ◆ Corrosion resistant Stainless Steel Diaphragm ◆ Flame Retardant Plastic ◆ Extended storage temperature ◆ Hermetically Sealed Alarm ◆ Water Proof, NEMA 3R, 4X, or 12 with Gasket (not supplied) ◆ RoHS, Lead Free Compliance ◆ ISO 9001 Certified 			
SPECIFICATIONS					
Operating Mode	Medium Loud, Fast Warble Tone		Pulse Rate	3 ± 10% Cycles per Second	
Operating Voltage	5 to 30 Vdc		Nominal Operating Voltage	24 Vdc	
Operating Frequency	Center Frequency 2,900 ± 250 Hz.; cycles approximately ± 300 Hz. From Center Frequency				
Typical Loudness	At Minimum Voltage	85 ± 5 dB(A), at 5 Vdc, 24 inches (61 cm), 25°C			
	At Maximum Voltage	98 ± 3 dB(A), at 30 Vdc, 24 inches (61 cm), 25°C			
Typical Operating Current	At Minimum Voltage	5 mA at 5 Vdc	At Maximum Voltage	25 mA at 30 Vdc	
	Operating Temperature	-30°C to +65°C		Storage Temperature	-40°C to +105°C
Surge Voltage	20% over maximum Operating Voltage for less than 5 minutes				
Materials	Alarm Case	Plastic, "A" Case, NORYL™, PX9406 or equal, flame retardant UL 94-V0, Black			
	Diaphragm	Stainless Steel 304			
	Encapsulation	Two parts epoxy resin or silicone potting, Black			
	Termination	Two, 0.25 (6.4 mm) Quick Connect Blades, 0.032Ø (0.8Ø mm) Wide, Brass, Electro-Tin plated With M3 0.25" (6.4 mm) long Stainless Steel Screws.			
Physical Dimensions	Length or Diameter (L/D)	1.46" (37.1 mm) Ø	Width (W)	Height (H)	1.4" (35.7 mm)
Approximate Weight	37 grams	Removable Washing Label	No	Compliance	RoHS
Available Options					
RELIABILITY					
Thermal Operating Temperature Test	240 hours continuous operation at Rated Power, at Maximum Rated Operating Temperature *				
	240 hours continuous operation at Rated Power, at Minimum Rated Operating Temperature *				
Thermal Storage Temperature Test	96 hours storage at Maximum Rated Storage Temperatures *				
	96 hours storage at Minimum Rated Storage Temperatures *				
Thermal Shock Test	5 cycles of Minimum and Maximum Operating Temperature				
	Each cycle shall be set per diagram below and is 3 hours long *				
Humidity Test	120 Hours at +60°C±2°C. 90-95% RH *				
Salt Spray	Withstand exposure to salt spray per ASTM B117 for a period of 300 hours *				
Water & Dust Exposure	Withstands water submergence and dust exposure per IP-68 *				
Vibration Test	2 Hours at 1.5 mm with 10 to 55 Hz. of vibration frequency to each of 3 perpendicular direction *				
Drop Test	Dropped naturally from 1 meter height onto the surface of 10mm wooden board, 2 directions upper and side of the part are applied *				
Termination Strength	Maximum of 15 pounds (6.8 Kg) load pull test and of 4 lb. per inch driving torque on screw				
* Reliability Test Performance	Parts should conform to original performance within ±3dB, after 3 hours of recovery and dry period				
Life Test	Intermittent	1,000 hours of a 1 minute on 4 minutes off cycle at room temperature and maximum rated voltage			
	Continuous	250 hours continuous operation at maximum rated Voltage and maximum Operating Temperatures			
Warranty	For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair				

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed.
 Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.



Current Draw and Loudness Vs. Input Voltage	DIMENSIONS	Units	Inches (mm)	Tolerance	0.030 (0.7)																																											
<p style="writing-mode: vertical-rl; transform: rotate(180deg);">Typical Output Sound Level ±4 dB(A), with Type 2 Meter</p> <p style="text-align: center;">Input Voltage (V)</p>	<p style="text-align: center;">FRONT VIEW RING NUT SIDE VIEW REAR VIEW</p>																																															
PACKAGING																																																
<p>ONE TRAY:</p> <p>TWO BUNDLE</p> <p>ONE BUNDLE:</p> <p>SHIPPING BOX</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>MODEL</td><td></td></tr> <tr><td>QTY</td><td>PCS</td></tr> <tr><td>N.W</td><td>KG</td></tr> <tr><td>G.W</td><td>KG</td></tr> <tr><td>SIZE</td><td></td></tr> <tr><td>LOT NO</td><td></td></tr> </table>	MODEL		QTY	PCS	N.W	KG	G.W	KG	SIZE		LOT NO		<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:50%;">MARKING</th> <th style="width:50%;">TRAY</th> </tr> </thead> <tbody> <tr> <td>Bundle</td> <td></td> </tr> <tr> <td>Customer PN</td> <td rowspan="3" style="text-align: center;">Dimensions</td> </tr> <tr> <td>Other PN if required</td> </tr> <tr> <td>Quantity</td> <td style="text-align: center;">42</td> </tr> <tr> <td>Lot and/or Date Code</td> <td style="text-align: center;">BUNDLE</td> </tr> <tr> <td>Bundle Number</td> <td></td> </tr> <tr> <td>Shipping Box</td> <td rowspan="3" style="text-align: center;">Dimensions</td> </tr> <tr> <td>Customer Part Number</td> </tr> <tr> <td>Other PN (if required)</td> </tr> <tr> <td>Quantity</td> <td style="text-align: center;">SHIPPING BOX</td> </tr> <tr> <td>Lot and/or Date Code</td> <td></td> </tr> <tr> <td>PO Number</td> <td rowspan="3" style="text-align: center;">Dimensions</td> </tr> <tr> <td>Net Weight</td> </tr> <tr> <td>Gross Weighjt</td> <td style="text-align: center;">1</td> </tr> <tr> <td>Box Number</td> <td style="text-align: center;">250</td> </tr> <tr> <td>of Number of Boxes</td> <td style="text-align: center;">9 Kg.</td> </tr> <tr> <td>Made in China</td> <td></td> </tr> </tbody> </table>	MARKING	TRAY	Bundle		Customer PN	Dimensions	Other PN if required	Quantity	42	Lot and/or Date Code	BUNDLE	Bundle Number		Shipping Box	Dimensions	Customer Part Number	Other PN (if required)	Quantity	SHIPPING BOX	Lot and/or Date Code		PO Number	Dimensions	Net Weight	Gross Weighjt	1	Box Number	250	of Number of Boxes	9 Kg.	Made in China				
MODEL																																																
QTY	PCS																																															
N.W	KG																																															
G.W	KG																																															
SIZE																																																
LOT NO																																																
MARKING	TRAY																																															
Bundle																																																
Customer PN	Dimensions																																															
Other PN if required																																																
Quantity		42																																														
Lot and/or Date Code	BUNDLE																																															
Bundle Number																																																
Shipping Box	Dimensions																																															
Customer Part Number																																																
Other PN (if required)																																																
Quantity	SHIPPING BOX																																															
Lot and/or Date Code																																																
PO Number	Dimensions																																															
Net Weight																																																
Gross Weighjt		1																																														
Box Number	250																																															
of Number of Boxes	9 Kg.																																															
Made in China																																																

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed.
 Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.