

## CI12E-07T230-C-6

Rev. 0-2023  
RoHS3 & REACH  
Electromagnetic Indicators





### Operating Characteristics

#### ELECTRICAL

Rated Voltage	5 VDC
Operating Voltage	3 to 7 VDC
Max Current at Vrated	35 mA

#### ACOUSTIC

Tone Category	Continuous
Description	Steady
Center $f$	2300 $\pm$ 300 Hz
Min SPL at Vrated	95 dB, Typ. 98 dB
Test Conditions	10 cm



### Physical Characteristics


#### MATERIALS

Housing	PBT (Black)
Diaphragm	Nickel Alloy
Through Hole Pins	Gold Plated Brass

#### TEMPERATURE RANGES

Operating	-20 to +70 °C
Storage	-30 to +80 °C

Weight 2 g



General tolerance =  $\pm 0.5$  mm and all measurements in mm unless otherwise noted.

Revision	Description	By	Date
0-2023	Original Specification	JL	2023-04-12

Warranty: For a period of one (1) year from date of shipping under normal operations conditions. This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.