


CI43P-30W310-C-1

Rev. 0-2023
RoHS3 & REACH
Piezoelectric Indicators



Operating Characteristics


ELECTRICAL

Rated Voltage	24 VAC/DC
Operating Voltage	16 to 30 VAC/DC
Max Current at Vrated	30 mA

ACOUSTIC

Tone Category	Continuous
Description	Steady
Center f	3100 \pm 500 Hz
Min SPL at Vrated	110 dB
Test Conditions	10 cm

Volts-SPL-Current



Physical Characteristics


MATERIALS

Housing	ABS
Diaphragm	Brass
Wires	UL 1007, 22AWG

TEMPERATURE RANGES

Operating	-20 to +60 °C
Storage	-30 to +70 °C

Weight 25 g



General tolerance = ± 0.5 mm and all measurements in mm unless otherwise noted.

Revision	Description	By	Date
0-2023	Original Specification	JL	2023-04-14

Warranty: For a period of one (1) year from date of shipping under normal operations conditions. This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.