

INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

CM05M-10T32-BA-1

Former P/N: CEM-OB5822-323G-XG01AC-00-0

Rev. 1-2019
RoHS3 & REACH
Omni Directional Microphones




Operating Characteristics

ELECTRICAL

Type	Analog
Rated Voltage	3.0 VDC
Operating Voltage	1.0 to 10 VDC
Capacitance	33 + 10 pF
Max Current	500 mA
Impedance	2000 Ω 1000 Hz

ACOUSTIC

Technology	Back Electret
Directionality	Omni Directional
Sensitivity	32 ± 3 dB
Min S/N	75 dB



Physical Characteristics


MATERIAL

Housing	Al-Mg Alloy
PC Pin	Gold Plated Copper

TEMPERATURE RANGES

Operating	-20 to +65 °C
Storage	-40 to +85 °C

Weight 0.2 g



Revision	Description	By	Date
1-2019	Migrate to new format	CF	2019-06-24

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.
©2019 Challenge Electronics, Inc. 20190826151905