

INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

CM03M-03S42-MA-2X

Former P/N: CM03OS-0342-A5

 Rev. 4-2020
 RoHS3 & REACH & IP67
 Omni Directional Microphones



Operating Characteristics

ELECTRICAL

Type	Analog
Rated Voltage	2 VDC
Operating Voltage	1.5 to 3.6 VDC
Capacitance	N/A
Max Current	0.1 mA
Impedance	300 Ω

ACOUSTIC @ 1000 Hz

Technology	MEMS
Directionality	Omni Directional
Sensitivity	-42 ± 3 dBV/Pa
Min S/N	58 dB



Physical Characteristics


MATERIAL

Solder Pads	Gold Plated Copper Foil
-------------	-------------------------

TEMPERATURE RANGES

Operating	-40 to +100 °C
Storage	-40 to +100 °C

Weight 0.03 g



Pick Area only extends to 0.25mm of any edge or hole unless otherwise specified

Pin 1	Pin 2	Pin 3	Pin 4
VDD	GND	GND	DAT

Revision	Description	By	Date
3-2019	Migrate to new format	CF	2019-08-14
4-2020	Added solder pad pin out. Corrected sensitivity from 42 dB to -42 dBV/Pa.	JL	2020-02-07

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.