

INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

CM03OS-0342-A3

Rev. 1-2018
RoHS & REACH
Omni Directional Microphones




Operating Characteristics

ELECTRICAL

Rated Voltage	2 VDC
Operating Voltage	1.5 to 3.6 VDC
Capacitance	N/A
Max Current	0.1 mA
Impedance	300 Ω
Test Condition	

ACOUSTIC

Technology	MEMS
Type	Analog
Directionality	Omni Directional
Sensitivity	42 ± 3 dB
Min S/N	59 dB




Physical Characteristics

TEMPERATURE RANGES

Operating	-40 to +100 °C
Storage	-40 to +100 °C

Weight	0.03 g
Termination	Surface Mount



Revision	Description	By	Date
0-2018	Initial Specification	JK	2018-06-14
1-2018	Migrate to new format	JK	2018-08-14

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.

©2018 Challenge Electronics, Inc. 20180926153212; Engine: 2; ALIAS: CM03OS-0342-MA3