



Powering Production Through Innovation



RUGGED AUDIO TECHNOLOGY

RESILIENT MATERIAL DURABLE ASSEMBLY THERMAL STABILITY

BUILT FOR HARSH ENVIRONMENTS



www.challengeelectronics.com

RUGGED PRODUCT LINE

	PART NUMBER SIZE (mm)	RUGGED FEATURE	IP RATING	TEMPERATURE (°C)
	CS32-01W130-10-1X 32.4Ø x 10.1	SEALED BACK SPEAKER	IP67	OPERATING: -40 to 85 STORAGE: -40 to 85
	CI35P-30E240-C-10X 35.2Ø x 41.8	FRONT PANEL MOUNT INDICATOR	IP68	OPERATING: -30 to 65 STORAGE: -40 to 90
	CT30P-30T260-1X 30.0Ø x 14.0	SEALED PIEZOELECTRIC TRANSDUCER	IP68	OPERATING: -40 to 85 STORAGE: -40 to 95
	CM06M-08W35-BA-1X 6.0Ø x 3.5	ENCAPSULATED MICROPHONE	IP67	OPERATING: -40 to 85 STORAGE: -40 to 85
	CAC42-03W42-28-2X 42.7 x 34.0 x 28.0	CHAMBERED SPEAKER ASSEMBLY	IP67	OPERATING: -30 to 85 STORAGE: -30 to 85



95 E. Jefryn Boulevard
Deer Park, NY 11729



(800)-722-8197



sales@challelec.com



challengeelectronics.com

Available On

