



# Artificial Intelligence Speakers

Acoustic Devices for AI Applications



INDICATORS • SOUND TRANSDUCERS • MICROPHONES • SPEAKERS • ASSEMBLIES

**Clear Vocal Range**

**Efficient Power  
Consumption**

**High Quality**

---

[www.challengeelectronics.com](http://www.challengeelectronics.com)

---

- Natural sounding audio output for clear human vocal reproduction
- Efficient operation for extended mobile usage
- Advanced speaker components for consistent reliability



## Speaker Recommendations



### CS19-02W100-03-1

Freq Range 800 to 20,000 Hz  
Rated SPL 105 ± 3 dB at 2 W



### CS28-02W57-07-1X

Freq Range 456 to 20,000 Hz  
Rated SPL 103 ± 3 dB at 2 W



### CS45-05D13-24-1X

Freq Range 104 to 20,000 Hz  
Rated SPL 104 ± 3 dB at 5W



### CAC32-02W110-13-1X

Freq Range 880 to 20,000 Hz  
Rated SPL 105 ± 3 dB at 2 W



### CAC32-02W90-16-1X

Freq Range 720 to 20,000 Hz  
Rated SPL 104 ± 3 dB at 2 W



95 E. Jeffryn Boulevard  
Deer Park, NY 11729



(800) 722-8197



sales@challelec.com



challengeelectronics.com

AVAILABLE ON

