

CT06E-01T300-1

Former P/N: CEET067A036-6-102-30P3R

Rev. 1-2019
 RoHS3 & REACH
 Electromagnetic Sound Transducers




Operating Characteristics

ELECTRICAL

Rated Voltage	1.5 Vo-p
Operating Voltage	1.0 to 1.7 Vo-p
Coil Resistance	6 ± 1 Ω
Max Current at V Rated	110 mA

ACOUSTIC

Min SPL at V Rated	70 dB
Test Conditions	10 cm
f _o	3000 ± 100 Hz



Physical Characteristics


MATERIAL

Housing	Noryl
Diaphragm	Ni-alloy
PC Pin	Copper

TEMPERATURE RANGES

Operating	-30 to +70 °C
Storage	-40 to +85 °C

Weight	1 g
--------	-----



Revision	Description	By	Date
0-2017	Initial Specification Sheet	JL	2017-10-11
1-2019	Migrate to new format	JK	2019-06-21

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.