


INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

## CT08E-06S400-1

Former P/N: CT08ES-06400-1

Rev. 0-2019  
RoHS3 & REACH  
Electromagnetic Sound Transducers




### Operating Characteristics

#### ELECTRICAL

Rated Voltage	5.0 Vo-p
Operating Voltage	1.0 to 6.0 Vo-p
Coil Resistance	13 ± 3 Ω
Max Current at V Rated	150 mA

#### ACOUSTIC

Min SPL at V Rated	100 dB
Test Conditions	10 cm
$f_o$	4000 Hz



### Physical Characteristics



#### MATERIAL

Housing	LCP (Black)
Diaphragm	Iron

#### TEMPERATURE RANGES

Operating	-40 to +85 °C
Storage	-40 to +85 °C

Weight	0.6 g
--------	-------



Revision	Description	By	Date
0-2019	Initial Specification Sheet	JL	2019-03-18

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.  
©2020 Challenge Electronics, Inc. Pub. 20200518144735