


CT09E-06T273-5

Rev. 0-2021
RoHS3 & REACH
Electromagnetic Sound Transducers




Operating Characteristics

ELECTRICAL

Rated Voltage	4 Vo-p
Operating Voltage	3 to 6 Vo-p
Coil Resistance	20 ± 3 Ω
Max Current at V Rated	100 mA

ACOUSTIC

Min SPL at V Rated	82 dB
Test Conditions	10 cm
f _o	2730 Hz



Physical Characteristics

MATERIAL


Housing	PBT
Diaphragm	Iron
Through-hole Pins	Red Copper

TEMPERATURE RANGES

Operating	-30 to +70 °C
Storage	-40 to +85 °C

Weight 1 g

Unless otherwise specified, tolerance: ± 0.5



All Measurements are mm unless noted otherwise.

Revision	Description	By	Date
0-2021	Original Specification	JL	2021-01-28

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.
©2021 Challenge Electronics, Inc. Pub. 20210202090420