


## CT10E-04T273-1

Former P/N: CEET108C040-15-204-27P4R

Rev. 2-2023  
RoHS3 & REACH  
Electromagnetic Sound Transducers




### Operating Characteristics

#### ELECTRICAL

Rated Voltage	3.0 Vo-p
Operating Voltage	2.0 to 4.0 Vo-p
Coil Resistance	15 ± 3 Ω
Max Current at V Rated	80 mA

#### ACOUSTIC

Min SPL at V Rated	90 dB
Test Conditions	10 cm
$f_0$	2731 Hz



### Physical Characteristics


#### MATERIAL

Housing	PPO Plastic Resin (black)
Diaphragm	Iron-Nickel Alloy
PC Pin	Gold Plated Brass

#### TEMPERATURE RANGES

Operating	-20 to +70 °C
Storage	-30 to +80 °C

Weight 1.0 g



All measurements in mm unless otherwise noted.

Revision	Description	By	Date
1-2019	Migrate to new format	JL	2019-06-21
2-2023	Added part image.	SK	2023-05-19

Warranty: For a period of one (1) year from date of shipping under normal operations conditions. This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.