


INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

CT14E-07W250-1

Former P/N: UAF-1405WLC-4

Rev. 2-2019
RoHS3 & REACH
Electromagnetic Sound Transducers




Operating Characteristics

ELECTRICAL

Rated Voltage	5 Vo-p
Operating Voltage	3 to 7 Vo-p
Coil Resistance	16 ± 4 Ω
Max Current at V Rated	75 mA

ACOUSTIC

Min SPL at V Rated	90 dB
Test Conditions	10 cm
f_o	2500 ± 200 Hz



Physical Characteristics


MATERIAL

Housing	Copper
Diaphragm	Iron
Wire	UL 1571, 26 AWG
Connector	Molex 51021-0200

TEMPERATURE RANGES

Operating	-30 to +85 °C
Storage	-40 to +85 °C

Weight 5 g



Revision	Description	By	Date
1-2018	Initial Specification Sheet	JL	2018-09-04
2-2019	Migrate to new format.	CF	2019-06-24

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.