

CT16E-08T204-2

Former P/N: CEET160B140-50-408-20P7.6LHR / CEET160B-408LHR

Rev. 5-2024
RoHS3 & REACH
Electromagnetic Sound Transducers




Operating Characteristics

ELECTRICAL

Rated Voltage	6.0 Vo-p
Operating Voltage	4.0 to 8.0 Vo-p
Coil Resistance	50 ± 6 Ω
Max Current at V Rated	40 mA

ACOUSTIC

Min SPL at V Rated	85 dB
Test Conditions	10 cm
f _o	2048 Hz



Physical Characteristics

MATERIAL


Housing	B style Plastic, Noryl
Diaphragm	Ni-alloy
PC Pin	Tin Plated Copper
Wash Label Included	

TEMPERATURE RANGES

Operating	-40 to +100 °C
Storage	-40 to +100 °C

Weight	5 g
--------	-----

Laser Engraving : CT16E-08T



General tolerance = ±0.5 mm and all measurements in mm unless otherwise noted.

Revision	Description	By	Date
4-2020	Added abbreviated former PN.	JL	2020-11-03
5-2024	Added the wash label in the mechanical drawing.	AL	2024-03-19

Warranty: For a period of one (1) year from date of shipping under normal operations conditions. This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.