

Tel: 1-800-722-8197 1-631-595-2217 Fax: 1-631-667-5484

EMAIL: sales@challelec.com WEB: www.challengeelectronics.com ISO 9001/14001:2015 Certified


INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

CT18P-18S200-1

Rev. 2-2022 **RoHS3 & REACH Piezoelectric Sound Transducers**



Operating Characteristics



Physical Characteristics

MATERIALS 18±0.3 Black PPS Housing 0.7 Diaphragm Nickel Alloy CT18P-1 Solder Tin Plated Pad Brass 0 TEMPERATURE RANGES Operating -40 to +105 °C -40 to +105 °C Storage 9.2 Weight 16.0±0.3 3 g

General tolerance = ±0.2 mm and all measurements in mm unless otherwise noted.

Revision	Description	Ву	Date
1-2022	Updated frequency response curve. Updated packaging diagram and photo.	СТ	2022-09-16
2-2022	Updated mechanical drawing and footprint dimensions.	СТ	2022-12-05

Warranty: For a period of one (1) year from date of shipping under normal operations conditions. This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.

©2022 Challenge Electronics, Inc. Pub. 20221205180157

