

**CS15-01W100-04-1X**

Rev. 0-2025  
RoHS3 & REACH  
IPX7 Front Face  
Mobile Speakers




**Operating Characteristics: Baffle Board**

**ELECTRICAL**

Rated Power	1 W
Short Term Max Power	1.2 W
Impedance	8 $\Omega$ $\pm$ 15 % 2,000 Hz; 1 W

**ACOUSTIC**

$f_o$	1,000 Hz $\pm$ 20 % 1 W
Freq. Range	800 to 20,000 Hz
Rated SPL	96 $\pm$ 3 dB 2,000 Hz; AVG; 1 W; 10 cm
Distortion	<10 % 2,000 Hz; 1 W



**Physical Characteristics**


**MATERIALS**

Housing	Stainless Steel + PPA
Cone	PEEK
Magnet	NdFeB
Wire	UL1571, 30 AWG
Connector	Molex:51021-0200 Or Equivalent

**TEMPERATURE RANGES**

Operating	-20 to +70 °C
Storage	-40 to +85 °C

Weight 1.5 g



General tolerance =  $\pm 0.25$  mm and all measurements in mm unless otherwise noted.

Revision	Description	By	Date
0-2025	Original Specification	KG	2025-02-25

Warranty: For a period of one (1) year from date of shipping under normal operations conditions. This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.