

CS19-02W100-03-1

Rev. 1-2024
RoHS3 & REACH
Mobile Speakers




Operating Characteristics: 1cc Sealed Enclosure

ELECTRICAL

Rated Power	2 W
Short Term Max Power	2.2 W
Impedance	8 Ω ± 15 % 2000 Hz; 2 W

ACOUSTIC

f_0	1000 Hz ± 20 % 2 W, 10 cm
Freq. Range	800 to 20,000 Hz
Rated SPL	105 ± 3 dB 1000, 1500, 2000 Hz; AVG; 2 W; 10 cm
Distortion	Max 10 % 2000 Hz; 2 W



Physical Characteristics


MATERIALS

Housing	PPA
Cone	PEEK
Magnet	NdFeB
Wire	UL1571, 30 AWG

TEMPERATURE RANGES

Operating	-20 to +60 °C
Storage	-20 to +70 °C

Weight 3.65 g



General tolerance = ±0.2 mm and all measurements in mm unless otherwise noted.

Revision	Description	By	Date
0-2024	Original Specification	AL	2024-02-27
1-2024	Weight updated from 3.0 to 3.65g.	AL	2024-03-18

Warranty: For a period of one (1) year from date of shipping under normal operations conditions. This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.