

INDICATORS • SPEAKERS • SOUND TRANSDUCERS • ENCLOSURES • MICROPHONES • BATTERY ACCESSORIES

## CS66-00D36-21-1

Former P/N: CES660S210BA08SPN360TR

Rev. 1-2019  
RoHS3 & REACH  
Square Speakers




### Operating Characteristics

#### ELECTRICAL

Rated Power	0.5 W
Short Term Max Power	1.0 W
Impedance	8 Ω ± 15 % 1000 Hz; 0.125 W

#### ACOUSTIC: Baffle Board

$f_0$	360 Hz ± 20 % 0.125 W
Freq. Range	360 to 3100 Hz
Rated SPL	94 ± 3 dB 1000, 1200, 1500, 2000 Hz; 0.1 W; 10 cm;
Distortion	<5 % 1000 Hz; 0.125 W



### Physical Characteristics


#### MATERIALS

Housing	Steel
Cone	Paper
Magnet	NdFeB
Solder Tab	Tin Plated Iron

#### TEMPERATURE RANGES

Operating	-20 to +55 °C
Storage	-30 to +60 °C

Weight 45 g



Revision	Description	By	Date
1-2019	migrate to new format	WS	2019-06-21

Warranty: For a period of one (1) year from date of shipping under normal operations conditions This warranty does not apply to products damaged through misuse, abuse, improper installation, alteration, rework, or attempt to repair.

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.  
©2019 Challenge Electronics, Inc. 20190826155217